

### SMART

- The Ultratorp Smart AKC comes with the new modular options
- The innovative activated carbon cartridges ensure you highest efficiency in hydrocarbon vapors adsorption as well as minimum residual water content to achieve low dewpoints in shortest time.

### RELIABLE

- With the built-in oil indicator you can check the exact residual oil content at any time
- Long lifetime and low maintenance

### EFFICIENT

- Flow-optimized and high efficient overall concept
- Easy service – all maintenance parts are easily accessible

## ULTRASORP SMART AKC

Activated carbon adsorber to remove oil vapors and hydrocarbons from the compressed air system. High operational safety ensured by the built-in oil indicator – exact residual oil content can be determined at any time. The new Ultratorp Smart AKC can be used as single solution or connected as a series.

**Excellence in performance – Innovative Concept - Smart Solution – Straightforward in Operation – Flexible**

## INDUSTRIES



- Industrial Machinery



- Packaging and Bottling



- Food Processing





- Automotive



- Energy

## MODULARITY

With the new modular options you can find the right position for your activated carbon adsorber the smart way.




## ROTATABLE INLET/OUTLET CONNECTION

Smart and easy inlet / outlet configuration by simply rotating the connection modules to the position that will fit your site. No modifications, no additional equipment, no investment.

## VARIABLE FILTER MODULES

Smart adsorber set-up. The filter modules are variable. adaptable. Space won't be a critical issue anymore.



## VERTICAL/HORIZONTAL OPERATION

The Ultrasorp Smart AKC can be installed either in vertical or horizontal orientation. Even the smallest space is suitable!



## ACTIVATED CARBON CARTRIDGES

### Reliable operation!


New activated carbon cartridge design in consideration of free flow in adsorbers. The flow-optimized design with low pressure drop is resistant against pressure and flow fluctuations. There is almost no start-up time to reach the required dew point. During service the compact activated carbon cartridges will be replaced one by one from the adsorber, so only small replacement space is needed. This gives additional advantages for your stock management.



### Service-friendly

The new Ultrasorp Smart AKC manifests itself through its service-friendliness. During services, the Ultrasorp Smart AKC remains firmly installed and within the pipeline, a safe execution and minimum downtime is ensured. No special tools are needed and all maintenance parts are easily accessible.




The overall concept is designed to keep it simple: all services are self-explanatory and time-saving!



## ULTRAPLEAT FILTER ELEMENTS


### Efficient operation!

The UltraPleat™ filtration technology uses a new structure of coated high-tech fibres that are processed into a pleated filter medium with a high separation efficiency of liquid particles and a huge adsorption capacity for solid particles. The multilayer structure of the new filter medium was designed so that optimal aerodynamic conditions are achieved, simultaneously providing a filter surface that is over 400% larger by comparison with wrapped filter media. For the separation of oil aerosols, an efficiency of up to  $\geq 99.9\%$  is achieved.




# ULTRASORP SMART AKC

## ULTRASORP SMART AKC DIMENSIONS



	Type	A mm	Weight kg	
			Plus	Superplus
MINI	0005	497	7	8
	0010	764	12	13
	0015	1031	18	19
	0020	1298	23	24
	0025	1565	28	29
MIDI	0035	866	28	30
	0050	1130	37	39
	0065	1394	46	48
	0080	1658	55	57
	0100	1922	64	66



	Type	B mm		C mm	D mm	E mm
		Plus	Superplus			
MINI	0005	268	314	125	204	157
	0010	268	314	125	204	157
	0015	268	314	125	204	157
	0020	268	314	125	204	157
	0025	268	314	125	204	157
MIDI	0035	398	464	180	309	233
	0050	398	464	180	309	233
	0065	398	464	180	309	233
	0080	398	464	180	309	233
	0100	398	464	180	309	233

# ULTRASORP SMART AKC

## PRODUCT DESCRIPTION

### Function description


Prefiltered, clean and dried compressed air (required inlet condition) is led via the inlet (I) and across the prefilter (1). At this stage, the air is cleaned from particles and condensate.

The condensate is removed via the condensate drain (2).

The air is led into the activated carbon adsorbers (3), in which the air will be cleaned from oil vapors and hydrocarbons.

The air gets into an afterfilter (4), in which possible particles from the activated carbon are retained. Via the built-in oil indicator (5), the saturation of the carbon can be measured at any time.

Via the outlet (O), the clean and dry air is led into the compressed air network to the point of use.



Superplus version with pre- and afterfilter (Plus version with afterfilter)

### Main Components

- 1 Prefilter UltraPleat™ (Superplus)
- 2 Condensate Drain (Superplus)
- 3 Activated Carbon Adsorber
- 4 Afterfilter UltraPleat™
- 5 Oil Indicator

## TECHNICAL DATA

	Type	Nominal Flow m <sup>3</sup> /h	Connection
MINI	0005	5	1/2"
	0010	10	1/2"
	0015	15	1/2"
	0020	20	1/2"
	0025	25	1/2"
MIDI	0035	35	1"
	0050	50	1"
	0065	65	1"
	0080	80	1"
	0100	100	1"

# ULTRASORP SMART AKC

## PRODUCT SPECIFICATION

Type	Nominal flow inlet m <sup>3</sup> /h	Prefilter UltraPleat™ S	Afterfilter UltraPleat™ S	Activated Carbon Cartridges QTY/Adsorber
0005	5	0035	0035	1
0010	10	0035	0035	2
0015	15	0035	0035	3
0020	20	0035	0035	4
0025	25	0035	0035	5
0035	35	0070	0070	2
0050	50	0070	0070	3
0065	65	0070	0070	4
0080	80	0120	0120	5
0100	100	0120	0120	6

## TECHNICAL CONFIGURATION

°C / bar g	4	5	6	7	8	9	10	11	12	13	14	15	16
20	0,91	0,99	1,08	1,16	1,23	1,30	1,37	1,43	1,49	1,55	1,61	1,66	1,72
25	0,89	0,98	1,07	1,15	1,22	1,29	1,36	1,42	1,47	1,53	1,59	1,65	1,70
30	0,83	0,97	1,06	1,13	1,21	1,27	1,34	1,40	1,46	1,51	1,56	1,62	1,67
35	0,63	0,75	0,88	1,00	1,12	1,25	1,33	1,39	1,45	1,50	1,55	1,60	1,65
40	0,38	0,45	0,53	0,60	0,67	0,75	0,80	0,83	0,87	0,90	0,93	0,96	0,99
45	0,22	0,26	0,31	0,35	0,39	0,44	0,47	0,49	0,51	0,53	0,54	0,56	0,58
50	0,13	0,15	0,18	0,20	0,22	0,25	0,27	0,28	0,29	0,30	0,31	0,32	0,33
55	0,08	0,10	0,11	0,13	0,15	0,16	0,17	0,18	0,19	0,20	0,20	0,21	0,21

**Example:**  $\dot{V}_{nom} = 22 \text{ m}^3/\text{h}$ , Inlet temperature = 25°C, Operating pressure = 12 bar (g)

$$\dot{V}_{corr} = \frac{\dot{V}_{nom}}{f} = \frac{22 \text{ m}^3/\text{h}}{1,47} = 14,97 \text{ m}^3/\text{h}$$

Calculated AKC size: Type 0015

<b>Functional Principle</b>	Fully-automatic
<b>Media</b>	Compressed Air / Nitrogen
<b>Operating Pressure</b>	min. 4 bar / max. 16 bar
<b>Media Temperature</b>	max. 55°C
<b>Ambient Temperature</b>	min. 4°C / max. 50°C
<b>Residual Oil Vapor Content</b>	≤ 0,003 mg/m <sup>3</sup> *
<b>Ambient Humidity</b>	max 100% at 50°C
<b>Operational Environment</b>	0-2000m NN (Indoor)

\*appropriate pre filtration and drying required, depending on application and operation conditions